



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

4MP IR Waterproof Bullet HD IP Camera, 3MP 2.8-12mm Varifocal Lens with IR CUT, POE Power Supply, VSS Mobile APP.



Model Number: RC-BM75V-4MPV-P

Main features:

28pcs IR LEDs (30M IR Distance).

3MP 2.8-12mm Varifocal Lens.

White casing with strong bracket.

Support IP66 waterproof.

Power in: POE/DC 12V.

Key specifications:

4MP 1/3'' OV4689 Low illumination CMOS+ HI3516D DSP.

Effective resolution: 2592(H)*1520P (V).

4MP\3MP HD resolution, clear and fine images.

Support 2D/3D noise reduction, digital wide dynamic.

H.265/H.264 video compression.

Super low rate, high-definition quality of image

Professional anti-lightning, conform to GB/T17626.5 and IEC61000-4-5.

Support cloud technology, easy to achieve network penetration, for in-line and alarm information pushed.

Support ONVIF2.6 protocol.

Provide web\CMS\center platform management software MYEYE, provide SDK development.

APP Name: VSS Mobile.

PC Client: IMS300

Product Advantages:

Offer 2-years product warranties.

Logistics convenient.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

OEM/ODM.
CCC/CE/FCC Certified.
Strict product quality control.
Efficiently working with almost NVR and HD Hybrid DVRs.
Lower price.
6-8 working day per order.

Product applications

The security products are widely used in many fields, in the office building, private villas, personal family and some public places (Park, street, square, etc.) can be used easily used to build and maintain, it will give you create a safe and comfortable environment.

Specification:

Descriptions	4MP HD Network Module
System structure	Embedded RTOS, dual-core 32bit DSP(Hi3516D), pure hard compression, watch dog
Sensor	4.0M 1/3" OV4689 low illumination CMOS; color 0.01Lux@F1.2, black/white 0.001Lux@F1.2
Video compression	H.265/H.264, support dual stream, AVI;0.1M~10Mbps variable;1~30f/s variable
Image output	Main stream:4MP 2592*1520@15fps; 3MP 2048*1536@25fps sub-stream: 704*576 @25fps
Noise reduction	Support 2D/3D
Wide dynamic	Support digital
Audio interface	1ch input, level:2Vp-p, impedance:1kΩ, support sound pick-up input;1ch output, impedance:16Ω,30mw, support microphone;
Audio compression	G.711, support bidirectional talk, audio and video synchronization;
Network interface	1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc.
USB interface	1*USB, support WIFI/3G
Auto iris	No
Signal interface	One photo resistance interface, one IR-CUT interface, support photo resistance signal and IR-CUT links to IR
PTZ	1*RS485, support kinds of PZT protocols
Alarm I/O	2/0 (support alarm input and video link to background)
SD Card	Unsupported
Anti-lightning	Power anti-lightning, conform to GB/T17626.5 and IEC61000-4-5
Other function	Support WEB, OSD, live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center reminder and image linkage, support JPEG capture; united remote client monitoring software、MYEYE; perfect SDK;
ONVIF	Support (Up to 2.6)
Mobile monitoring	Support multiple mobile monitoring (iOS, Android)
Other	DC12V/2A input (Support POE power supply), power consumption: ≤3W, dimension