SHENZHEN RISE ELECTRONIC CO., LTD.
Website: http://www.ideacamera.com Email:cctv@ideacamera.com
Global Sources Homepage Address: http://www.globalsources.com/ideacamera.co

5MP 10Inch AI Tracking High Speed Dome IP Camera, 3D human tracking, P6SLite APP, 18X Optical Zoom Lens, Waterproof IP66.





Model: AT-H8612F-5MP-18X

Key features:

5MP 3D human tracking
Resolution: 2592x1944@20fps/2592x1520@15fps
18X optical zoom(4.35mm~96.3mm)
IR distance 200 meters
6units IR leds+4units Laser LED+4units Warm light leds(Dual Light)
10inchs, Half Metal Housing, IP66
Support 3D human tracking
Support P2P real-time message push
Support 18X optical zoom, POE for optional
Built in two-way audio function, intrusion warning prompt
ONVIF, Compatible with HIKVISION, DAHUA, Raysharp, TVT, AEVISION NVR etc.
Intelligent IR illumination & power consumption is variable, dependant the zoom factor
APP：P6SLite

Product Advantages:

Offer 2-years product warranties.
Logistics convenient.
OEM/ODM.
CCC/CE/FCC Certified.
Strict product quality control.
Efficiently working with almost Hybrid DVR.
Lower price.
6-8 working day per order.

Product applications:

This is the best product of safety field. It and hard disk video recorders、cable、power supply、

display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

Camera	
Resolution	2592x1944@20fps 2592x1520@15fps
Sensor	Hi3516E+Sony335
Optical Zoom	18X F=4.35mm~96.3mm
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
DNR	2DNR, 3DNR
WDR	DWDR
S/N Ratio	≥50dB
Dome	
Communications Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
Remote Control	Android, iPhone
Software Control	IE, EasyVMS, P2P(P6SLite)
Rotation Range	Pan: 0°~360°, Tilt: 0°~93°
Rotation Speed	Pan: 0~200°/s, Tilt:0~100°/s
Auto Flip	Support
Preset Points	220pcs presets (dwell time 01-60s interval available)
A-B scan	User programmable (scan speed 1-64 levels setting available)
Guard Tours	3 groups (Max.16 points, dwell time user selectable)
Tracking Distance	5-45M
Tracking Speed Range	3-12KM/h
3D Tracking Region	A single point trigger / 1-16pcs multipoint trigger
Audio	Built-in Two-way Audio; Audio Alarm Prompt

Operating temperature	-40º~+60ºC
Operation menu	English
Power	DC 12V 5A
Consumption	≤25W
IR distance	Up to 200 Meters
LEDs	6units IR leds+4units Laser LED+4units Warm light leds(Dual Light)