



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

4MP 10Inch IP PTZ High Speed Dome Camera with wiper, P6SLite APP, Low temperature, 18X Optical Zoom Lens, P2P, Waterproof IP66.



Model: RP-H8620-4MP-18X

Key features:

High performance chip (1/3" CMOS 4MP FH8852V200+GKW4653).

4MP PTZ High Speed Dome IP Camera.

18X Optical Zoom Lens (4.35-96.3mm).

Efficient Resolution: 2688(V)*1520P (H).

H.264/H.265M Video Compression.

10PCS IR LED+5PCS Laser LED, 150M IR Distance.

Rotation Range (Pan: 0°~360°, Tilt: 0°~93°).

Rotation Speed (Pan: 0~200°/s, Tilt: 0~100°/s).

Auto Flip: Horizontal 180°, Vertical 93°.

Support P2P function.

10" full metal body construction, IP66.

Optional function: Audio

ONVIF; Compatible with HIKVISION, DAHUA, Raysharp, TVT, AEVISION NVR etc.

Product Advantages:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Efficiently working with almost Hybrid DVR.

Lower price.

6-8 working day per order.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Product applications:

This is the best product of safety field. It and hard disk video recorders、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community、or a large public places, etc.

Camera	
Solution	1/3" CMOS 4MP FH8852V200+GKW4653
Output Pixel	2688*1520@20fps
Lens	18X f=4.35mm~96.3mm, optical zoom
Illumination	Color: 0.02Lux B/W:0.002Lux
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
DNR	2DNR, 3DNR
WDR	DWDR
S/N Ratio	≥50dB
Dome	
Communications Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
Software Control	IE, EasyVMS, P6SLite
Mobile View(optional)	Support Windows, iPhone platform smartphone
Video compression	H.265/M-JPEG
Rotation Range	Pan: 0°~360°, Tilt: 0°~93°
Rotation Speed	Pan: 0~200°/s, Tilt:0~100°/s
Medium Speed	Pan:0~80°/s, Tilt:0~40°/s
Auto Flip	Horizontal 180°, Vertical 93°
Preset Points	220pcs presets (dwell time 01-60s interval available)
A-B scan	User programmable (scan speed 1-64 levels setting available)
Guard Tours	3 Groups (Max.16 points, dwell time user selectable)
Operating temperature	-40°C~+60°C
Operation menu	English
Power	DC 12V 5A
Consumption	≤20W
Lightning Protection	Transient voltage 6000V
IR parameters	
Auto Control IR LED	PWM



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

IR distance	Up to 150meters
LEDs	10PCS IR LED+5PCS Laser LED