

1.0megapixels 720p Wireless smart camera,Support 433 alarm, E-Mail alarm, Motion detection, Manual recording, Alarm recording, With 2MP 3.6mm HD Fixed Lens, Support night vision, Support TF Card local storage (Max to 64G), Support remote control, PC client control.

Model: RC-WPTD-1MP



Product key features

- Support wireless WIFI Internet connection, at a corner of the house, the store.
- Effective pixel is 1280*720p, with 2.0megapixels 1080p HD lens.
- Support mobile phone or PC computer client operation.
- Support intelligent online, one key to set up a wireless connection, easy to work.
- Support TF storage (Max to 64GB).
- Support dynamic bit rate adjustment, video file size changes with the change of scene complexity, in order to save the storage space.
- Support motion detection alarm, alarm can automatically send E-mail and phone APP to

push.

- Support network function for fashion.
- Video format for MP4, the video file can be open by storm, Real player etc.
- Support voice intercom and monitoring etc.
- Support night vision, built-in double filter, and IR-CUT automatic switch, with 11pcs IR LEDs.
- Support PTZ control, horizontal rotating 355 degrees, and vertical rotating 355 degrees.
- Support website upgrade or file upgrade.

Product main applications

Widely used in various types of residential area (such as villas, communities etc.)、small and medium-sized indoor spaces (small and medium-sized stores、small and medium-sized company office area etc.)

Product main parameters

Model		RC-WPTD-1MP
Display	Image sensor	1/4"CMOS
	Video resolution	1280×720
	Effective pixel	1megapixels
	Video compression standard	H.264/JPEG
	Video frequency	Max to 25fps
	Video bit rate	64Kbps ~ 8Mbps
	S/N	44dB
	Minimum illumination	0Lux(IR ON)
Lens	Interface size	M12
	Length collection	3.6mm
	Length viewing angle	90°
	Focus system	prime
Function	Privacy shelter	Each channels support 4 occlusion area block at the same time
	Exposure control	automation
	Gain control	automation
	White balance	automation
	Voice intercom	support
	D/N functionality	IR-CUT double filter switch , support colors turn to black.
	Video adjustment	Support contrast、luminance、saturation、acutance or picture image etc.
	Remote operation	System setting、stream management、storage management、user management、network management
	Mobile detection	support

	433 alert function	support (optional)
	Detection alert	E-mail alert、client alert、FTP alert
	Local storage	Mat to 32G
Network	Ethernet	10/100M Ethernet
	Stream	Three stream
	Internet protocol	Standard HTTP.TCP/IP.ICMP.RTSP.RTP.UDP.RTCP.SMTP.FTP.DHCP.DNS.PPPOE
	Wireless network	Wi-Fi
	Internet transmission	Built-in cloud monitoring transmission protocol
Hardware interface	Audio input	Built-in 1 MIC
	Audio output	Built-in 1 speaker
	Reset	Restore the default settings
	Internet interface	1 RJ45
	Wireless interface	1 Wi-Fi extremal antenna interface
PTZ	Rotation	horizontal : 355°、vertical : 100°
Environment	Temperature	-20℃ ~ +55℃
	Humidity	10% ~ 90%
Basic feature	Infrared LEDs	11pcs LEDs
	Infrared distance	10 ~ 30 meters
	Power	DC 5V
	Maximum powerful	≤3.65W
	Color/material	white /ABS plastic
	Size	100×135×128mm
	Weight	300g
	Installation	Bracket installation、desktop installation、lifting