



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

**2MP HD Vehicle Infrared Panoramic Camera, 3MP 1.39mm
Panoramic Lens, 360° Vertical View, 180° Horizontal View,
IP66 Outdoor Use, All Metal Housing, Top Good Quality.**



Model: VR-VAHD360K-2MP

Main Features:

Black All Metal Housing

12pcs \varnothing 5 IR LEDs(15M IR Distance).

3MP 1.39mm HD Panoramic Lens.

BNC Interface Video Cable (OSD Menu optional).

Key specifications:

Image sensor (1/2.8 inch Sony IMX323 +2441H)

Output AHD/TVI/CVI/CVBS, Effective resolution is 1920*1080p.

OSD menu supports 12 different languages.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Strong light inhibition/privacy protection.

BLC/DPC, 2D noise reduction function.

OSD function (mirror image, color/ white-black, PAL/NTSC).

UTC Function (Working by Hybrid DVRs).

AGC type, day-night effect is distinct, various day-night modes can be switched by OSD menu With D-WDR.

Support UTC, 4-in-1, switched by OSD, Enhancement adjustment supported by OSD.

Power (600W) & Video (2KV) dual-lightning protection design, OSP antioxidant PCB, size 38*38 Dual-border.

Production Advantages:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Work with almost HD 5IN1 Hybrid DVRs.

Lower price.

6-8 working day per order.

Production applications:

This is the best product of safety field. It and hard disk video recorders、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

Specifications:

Descriptions	1080P HD Analog Video Camera Module
Sensor	1/2.8 inch Sony IMX323 +2441H sensor
Video Resolution	PAL/NTSC : 1920(H)*1080(V)
Minimum Illumination	color: 0.01Lux@ (F1.2, AGC ON) , 0Lux with IR
	Black & White: 0.001Lux@ (F1.2, AGC ON) , 0Lux with IR
Photosensitive Resistance	1 photosensitive resistance interface, support the photosensitive resistor input signal and image, IR-CUT,
Shutter	1/50(1/60) seconds to 1/100,000 seconds



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Day and Night Function	Support IR-CUT
Lens Parameters	C/CS interface, M12 lens optional
Synchronous Mode	inter-sync
Noise-signal Ratio	>58dB
BLC	AUTO
AWB	AUTO
Video Output	AHD/CVI/TVI/CVBS
Temperature and Humidity	- 10 °C~ 60 °C, humidity is less than 90% (no condensation)
Power	DC12V±10%
Consumption	<5W
Size	Standard 38*38 positioning hole8