



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

5MP H.265 IR Bullet IP Camera with Audio In, 5MP 2.8-12mm varifocal Lens, Internal POE, Support Face Detection, VSS Mobile Cloud App.



Model: RC-BM75V-5MPO-P-A

Key features:

- 5MP 2.8-12mm varifocal lens.
- White all metal body with strong bracket.
- Built-in 28pcs IR LEDs.
- Support 30meters IR distance.
- Internal POE with audio in.
- High quality network video cable.

Main parameters:

- 32-bit DSP (1/2.7"OS05A10+3516D Sensor).
- 2560*1440@18fps High resolution.
- Support Face Detection (all channels in VSS system).
- Mobile APP Name: (VSS Mobile).
- Computer operation client (IMS300).
- Support ONVIF protocol (up to 2.6).
- H.265/H.264 high profile.
- Support Tri-Stream technology.
- Support one channel audio input, one channel audio output, support two-way voice speaking.
- Support one channel alarm input, one channel alarm output.
- Support one TF card interface, the maximum up to128G.
- Support one electric zoom interface.
- Support one 485 interface.
- Support one USB interface.
- Support one CVBS output.
- Support SMART IR.



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Support 3D DNR, DWDR.

Support P2P and cross-browser access.

Product Advantages:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Efficiently working with almost NVR.

Lower price.

6-8 working day per order.

Product applications:

This is the best product of safety field. It and hard disk video recorders、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community、or a large public places, etc.

Specifications:

5MP IP Module		
Product model	RC-BM75V-5MPO-P-A	
System Structure	DSP	Embedded RTOS, DSP(Hi3516D)
	Sensor	1/2.7" CMOS sensor (OS05A10)
Video Encoding	Video Encoding	H.265 Main Profile H.264HighProfile/ Main Profile/ BaseLine Profile
	Maximum Image Output	Main stream: 2560*1440@18fps; Auxiliary stream one and two can optional
	Video Bite rate	32Kbps~8MKbps
Image Enhancement	Min. illumination	Color <u>0.1Lux@F1.2</u> (AGC ON); black and white <u>0.01Lux@F1.2</u> (AGC ON)
	Electronic shutter	Auto (1/25 to 1/10000)
	Day/Night switch	Auto/color/B&W (Built-in IR_CUT)
	DNR	2D and 3D DNR
	WDR	Support digital wide dynamic and REAL wide dynamic
	Video Adjust	Sharpness, Brightness, Saturation, Contrast Adjustable



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Interfaces	Signal interface	one photosensitive resistance signal interface, one IR_CUT drive interface support photo resistance signal links to IR-CUT and IR light
	Smart IR	One port
	Reset interface	One port
	Audio interface	One audio in; One audio out
	Alarm interface	One alarm in; One alarm out
	electric zoom interface	One port
	Power interface	One DC12V power input
	CVBS Interface	One Port
	USB interface	One Port
	POE interface	One Extended Interface
	Network lamp interface	One Port
	Network interface	One RJ45 10/100M Port
Functions	Motion detection	Multiple detection zones, variable sensitivity levels
	Capture function	JPEG, capture resolution is the max coding resolution
	Security	Password protection and water marker
	OSD	Support Channel Name and Time
	Smart function	Tripwire、Regional invasion、Items stolen、Items move、 Density Detection、Number Stat、Through fence、Loitering Detection、Retrograde、Face Capture
	Smart alarm	Network abnormal, cover alarm etc.
	Mobile client	VSSMOBILE for both iPhone and Android system phone
	Protocol support	TCP/IP; UDP; HTTP; IGMP ; ICMP; DHCP; RTP/RTSP; DNS; DDNS; FTP; NTP; PPPOE; UPNP; SMTP; SNMP
Interface protocol	ONVIF/CGI/GB28181	
General	Power Supply	DC12V/POE(-P)
	Power Consumption	<1.7W (without infrared lamp board)
	Lightning Protection	Power, network, POE all lightning protection, meets with standard GB/T17626.5, and IEC61000-4-5
	IR_CUT pitch	20mm



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

	Size	38*38 (mm) Single Board
--	------	-------------------------