



## SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: [cctv@ideacamera.com](mailto:cctv@ideacamera.com)

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

**5MP 6Inch AI Tracking High Speed Dome IP Camera, 3D human tracking, P6SLite APP, 18X Optical Zoom Lens, Waterproof IP66.**



**Model: AT-H808F-5MP-18X**

**Key features:**

5MP 3D human tracking

Resolution: 2592x1944@20fps/2592x1520@15fps

18X optical zoom(4.35mm~96.3mm)

IR distance 120 meters

9units Warm light leds

6inchs, Half Metal Housing, IP66

Support 3D human tracking

Support P2P real-time message push

Support 18X optical zoom, POE for optional

Built in two-way audio function, intrusion warning prompt

ONVIF, Compatible with HIKVISION, DAHUA, Raysharp, TVT, AEVISION NVR etc.

Intelligent IR illumination & power consumption is variable, dependant the zoom factor

**APP: P6SLite**

**Product Advantages:**

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Efficiently working with almost Hybrid DVR.

Lower price.

6-8 working day per order.

**Product applications:**



## SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: [cctv@ideacamera.com](mailto:cctv@ideacamera.com)

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

This is the best product of safety field. It and hard disk video recorders、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

Camera	
Resolution	2592x1944@20fps 2592x1520@15fps
Sensor	Hi3516E+Sony335
Optical Zoom	18X F=4.35mm~96.3mm
BLC	Support
AGC	Auto/manual
WB	Auto/manual/indoor/outdoor
DNR	2DNR, 3DNR
WDR	DWDR
S/N Ratio	≥50dB
Dome	
Communications Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
Remote Control	Android, iPhone
Software Control	IE, EasyVMS, P2P(P6SLite)
Rotation Range	Pan: 0°~360°, Tilt: 0°~93°
Rotation Speed	Pan: 0~200°/s, Tilt:0~100°/s
Auto Flip	Support
Preset Points	220pcs presets (dwell time 01-60s interval available)
A-B scan	User programmable (scan speed 1-64 levels setting available)
Guard Tours	3 groups (Max.16 points, dwell time user selectable)
Tracking Distance	5-45M
Tracking Speed Range	3-12KM/h
3D Tracking Region	A single point trigger / 1-16pcs multipoint trigger



## SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: [cctv@ideacamera.com](mailto:cctv@ideacamera.com)

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

Audio	Built-in Two-way Audio; Audio Alarm Prompt
Operating temperature	-40°~+60°C
Operation menu	English
Power	DC 12V 4A
Consumption	≤25W
IR distance	Up to 120 Meters
LEDs	9 pcs Warm LED